

The DisplayPort AOC is the perfect solution for extending DisplayPort signals in classrooms, conference rooms, healthcare facilities, digital signage and other commercial environments.

Convenience

Utilizing AOC technology that performs similar to traditional copper cabling, the optical fiber construction between the connectors provides optimum performance and easy installation. The AOC technology delivers several advantages which make it a smart choice in select installations. The cable diameter is smaller than copper and more flexible, making it easier to install in tight spaces. Constructed from fiber strands, this cable reduces the risk of EMI/RFI so performance is stable when used in typically high interference environments such as data centers, surgical theaters, or manufacturing facilities where high resolution and consistent display are critical.

Performance

The AOC draws power from the DisplayPort source device, so no external power source is required. In addition to low power consumption, these cables are also plug and play and hot swappable. Additionally, the DisplayPort Active Optical Cable supports the latest 4K (4096 x 2160 at 60Hz) content delivery over longer distances.

No external power required

Supports 3D Video, Deep Color and x.v.Color

Features & Benefits

Supports resolutions up to 4K (4096 x 2160 at 60Hz)

CEC, EDID, and HDCP compatible

Plenum rated jacket

Specifications

General Info

| Product Line | C2G | Color | Black |
|--------------------|-------------------------|-------------------|--------------------|
| UPC Number | 757120295389 | Country Of Origin | Korea, Republic Of |
| Application Sector | Commercial, Residential | Warranty Type | 5-Year |
| Туре | Active Device, Cable | | |
| Dimensions | | | |
| Product Length US | 100.0 FT | Cable Length | 100 ft |
| | | | |



Technical Information

| Jacket Material | PVC (Polyvinyl Chloride) | Video Resolution | 1080p, 4K, 4K 30Hz, 4K 60Hz |
|--------------------|-----------------------------------|--------------------|-----------------------------|
| Jacket Application | Plenum Rated | Bend Radius | 5 mm |
| Cable Type | Active Optical Cable (AOC), Video | Jacket Rating | CMP Rated, FT6 Rated |
| Cable Diameter | 5.1 mm | Data Transfer Rate | 21.6 Gbps |
| Adapter Rear | DisplayPort Male | Adapter Front | DisplayPort Male |