

C2G 12ft (3.7m) 75 Ohm BNC Cable

Part No. CG-40027



A high quality BNC cable for video applications including CCTV, broadcast, studio, boardroom presentations, home theater, etc. Manufactured from 75 Ohm RG59/U dual shield coax cable (60% copper braid over foil) with a 22 AWG copper-covered steel center conductor. Finished with bright nickel-plated BNC connectors that have molded PVC strain relief to protect the cable from wear over time.

Features & Benefits

RG59/U Dual Shield coaxial cable

Nickel-plated BNC connectors

Constructed with a 75copper conductor

Molded PVC strain relief

Specifications

General	Info
---------	------

Product Line	C2G	Color	Black
UPC Number	757120400271	Country Of Origin	Vietnam
Application Sector	Commercial, Industrial, Residential	Warranty Type	Lifetime
Туре	Cable		

Dimensions

Draduct Langth IIC	12.0 FT	Cabla Lanath	10 ft
Product Length US	12.0 F1	Cable Length	1211

Technical Information

Jacket Material	PVC (Polyvinyl Chloride)	Wire Gauge	22 AWG
Cable Type	Video	Jacket Rating	Standard / Non-Rated
Cable Diameter	6 mm	Adapter Rear	BNC Male
Adapter Front	BNC Male		

