



Use this XLR to XLR cable to connect unbalanced sources to balanced XLR inputs. This pro-audio cable is made from 22 AWG twisted pair audio cable under an aluminum foil shield and 60% copper braid for maximum shielding from noise. The highly flexible 7mm PVC jacket reduces the risk of the cable kinking and damaging the conductors.

Bright nickel plating on solid brass connectors resists wear from reconfiguring and moving equipment from one venue to another. Spring strain relief on the 1/4in plug and a chuck strain relief inside the XLR reduce the effects of age on the solder joints and contacts.

Features & Benefits

22 AWG conductor construction

Foil and braided shield to protect from interference

Highly flexible jacket

Nickel-plated connectors

Specifications

General Info

Product Line	C2G	Color	Black
UPC Number	757120400592	Country Of Origin	Vietnam
Application Sector	Commercial, Residential	Warranty Type	Lifetime
Type	Cable		

Dimensions

Product Length US	6.0 FT	Cable Length	6 ft
-------------------	--------	--------------	------

Technical Information

Jacket Material	PVC (Polyvinyl Chloride)	Cable Type	Adapter, Audio
Jacket Rating	Standard / Non-Rated	Adapter Rear	XLR 3-pin Female
Adapter Front	XLR 3-pin Male		