



Audio installations in educational and commercial settings often require in-wall rated cable. Our CMG-rated line was specifically engineered to meet this requirement while overcoming common challenges faced by installers in these environments. Low-Profile connectors (1.41in total depth) save valuable space in the gang box.

This cable is constructed from 22 AWG twisted pair wire and drain wire. The entire cable is foil shielded to ensure signal integrity.

CMG rated cables meet many NEC requirements for Communications Cables General Purpose In Wall Use. Our cables meet the following ratings: CMG, FT4, CM, CL3, CL2, CMX, CL3X, and CL2X.

Always check with your local authority on building requirements to verify cable requirements before beginning any installation.

Features & Benefits

In-wall, CMG-Rated jacket	22 AWG conductor construction
Low-profile connectors	Supports a Stereo Audio signal

Specifications

General Info

Product Line	C2G	Color	Black
UPC Number	757120401100	Country Of Origin	Vietnam
Application Sector	Commercial, Residential	Warranty Type	Lifetime
Type	Cable		

Dimensions

Product Length US	75.0 FT	Cable Length	75 ft
-------------------	---------	--------------	-------

Technical Information

Jacket Material	PVC (Polyvinyl Chloride)	Jacket Application	In-Wall Rated
Cable Type	Audio	Jacket Rating	CMG Rated, FT4 Rated
Adapter Rear	3.5mm Stereo Male	Adapter Front	3.5mm Stereo Male