

This amplifier has been designed to mount under a desk, in a podium, or to nearly any flat surface with the ability to control the volume from a decorative style wall plate. This simple discreet solution provides sound reinforcement from a concealable amplifier capable of filling a class room, meeting room, huddle space, or work shop with rich sound while offering a convenient remote control that can be installed within reach.

Send in the reinforcement

In a crowded room a speakers voice can quickly be lost to the noise. Ensure that every word can be heard with this simple audio reinforcement amplifier. Each word will be launched at the audience with 15 watts of power at 4Ω resistance providing distinct audio to all listeners.

Command amplitude

There is no need to search for controls or fiddle with settings when preparing to present. The remote control wall plate can be installed in the location that is most convenient to a presenter, ensuring a smooth start to any meeting.

Need more input

Dynamic presentations may require more than dazzling vocals to deliver the intended message. This amplifier incorporates a 3/4 inch microphone port and a 3.5mm stereo audio line level input, offering the ability to deliver reinforced content from an audio source such as a laptop or a triumphant oration leaving the audience astounded.

Effortless deployment

This amplifier simplifies audio reinforcement installation. No brackets or field terminations are required with this amplifier. Simply secure the amplifier with the built in mounting brackets to the desired location, attach speaker wires, and plug in a cat5e or cat6 cable to connect the remote control wall plate.



Features & Benefits

15 watts (RMS) per channel

Remote wired wall plate controller

1/4" dynamic microphone and 3.5mm stereo audio line level inputs

Built in mounting bracket

Specifications

General Info

Product Line C2G

Color White

Country Of Origin Taiwan, Province Of China

Application Sector Commercial, Residential

Warranty Type Lifetime

Type Amplifier

Dimensions

Product Width US 2.74 in

Product Depth US 0.25 in

Product Height US 4.48 in

Listing Agencies / 3rd Party Agencies

CE Certified Yes

FCC Compliant Yes

REACH Compliant Yes

Buy American Act Compliance

TAA Compliant Yes

Technical Information

Amperage 2 A

Adapter Rear RJ-45 Female

Adapter Front RJ-45 Female, 3.5mm Stereo Female, Screw Terminal Block, 1/4in TRS Female
