

HDMI® HDBaseT + USB-B and RS232 over Cat Extender Single Gang Wall Plate Transmitter to Box Receiver - 4K 60Hz allows a 4K HDMI source to be extended up to 130ft to a 4K display using a single Cat6a Ethernet cable. This is an ideal solution where USB must also be extended alongside HDMI video and audio to interactive whiteboards and displays in conference rooms, classrooms, lecture halls, and many other installation needs far beyond the length limitations of standard HDMI cabling.

This HDBaseT kit extends HDMI and high speed USB 2.0 over a single Cat5e, Cat6, or Cat6a network patch cable. Extend 4K HDMI up to 115 feet and 1080p up to 230 feet using a Cat5e or Cat6 cable. For longer 4K distances, extend 4K HDMI up to 130 feet using a Cat6a cable. Extend USB 2.0 pass through up to 230ft, connecting up to 4 USB devices to the receiver.



This kit is HDCP 2.2 compliant, making sure that the connection from the source is secure. Multi-channel audio formats are supported, including PCM 2.0/5.1/7.1, Dolby TrueHD, Dolby Atmos, DTS-HD Master Audio, and DTS:X. High speed USB 2.0 pass-through supports up to 230ft for KVM control of devices such as USB cameras, keyboards, mice, etc. With one-way Power over HDBaseT (PoH) support, the transmitter gets its power from the receiver, so no additional power adapter is required, allowing for greater installation flexibility. Advanced users can control RS232 pass-through to pass RS232 commands between the wall plate and the receiver. The receiver toggle switch also allows for the selection of upgrades that can upgrade both the wall plate and receiver.

Note: Ensure a solid, reliable connection between the 4K HDMI HDBaseT Extender and critical equipment. We suggest using HDMI Cables with gripping connectors that provide greater port retention than standard HDMI connectors.

Note: Stranded Cat5e/6/6a patch cables may be used for HDMI extension applications up to 230ft. Shielded, solid conductor Cat6 or HDBaseT Certified Cat6a network cabling is recommended for applications where the category cable must be coiled, is run near other high-frequency signaling cables, or in high EMI/RFI environments. For best performance use an [HDBaseT Certified Cat6a Patch Cable](#).

Features & Benefits

Extend 4K at 60Hz (4:4:4) up to 130ft and 1080p at 60Hz up to 230ft with Cat 6a cable	Extend 4K at 60Hz (4:4:4) up to 115ft and 1080p at 60Hz up to 200ft with Cat 5e/6 cable
HDCP 2.2 compliant, to create a secure connection between the source and display	Supports multi-channel audio formats, including PCM 2.0/5.1/7.1, Dolby TrueHD, Dolby Atmos, DTS-HD Master Audio and DTS:X
Supports EDID from the HDMI out	Supports CEC pass-through, allowing central control to all HDMI compatible devices
Supports USB 2.0 pass through over HDBT up to 230ft, connecting up to 4 USB devices to the receiver	Supports one-way Power over HDBaseT (PoH), so that the wall plate can be powered by receiver
RS232 pass through mode can pass the RS232 command between wall plate and receiver	Toggle Switch (receiver only) used to select RS232 port function - RS232 pass through or upgrade
Upgrade mode can update both wall plate and receiver	

Specifications

General Info

Product Line	C2G	Color	White
UPC Number	757120300243	Country Of Origin	China
Features	RS232	Application Sector	Commercial
Warranty Type	5-Year	Type	Active Device, HDBaseT, Transmitter

Dimensions

Product Width US	9.64 in	Product Depth US	3.55 in
Product Height US	0.98 in		

Technical Information

Video Resolution	1080p, 1080p 60Hz, 4K, 4K 30Hz, 4K 60Hz	Data Transfer Rate	18 Gbps
Adapter Rear	HDMI Female, USB-A Female, USB-A Female, RJ45 Female, USB-A Female, USB-A Female, DC Power Plug	Adapter Front	DC Power Plug, RJ45 Female, USB-B Female, HDMI Female
Operating Temperature	0°-45°C	Storage Temperature	-20° - 70° C
