

C2G

1ft (0.3m) TAA-Compliant F-Series Cat5e Snagless Unshielded (UTP) Network Cable - Blue Part No. AVD CG C2G43408



This Cat5e cable meets stringent TAA compliant requirements and is approved for use in United States government projects and facilities. This Snagless Unshielded Cat5e network cable is designed for network adapters, hubs, switches, routers, servers and more. Meets or exceeds all ANSI/TIA-568.2-D Category 5e industry standards for supporting a wide variety of applications, including 1000BASE-T (1 Gigabit Ethernet). Constructed with premium, made in the USA copper cabling with enhanced 350 MhZ maximum frequency for increased performance over standard Cat5e cables. The molded, snagless boot prevents unwanted cable snags during installation and provides extra strain relief.

Features & Benefits

TAA-compliant

Constructed with high quality, made in the USA raw cable for consistent, reliable performance

Snagless RJ45 connector design protects clips from being easily snapped Standard RJ45 connectors and unshielded twisted pair off – great for applications with high insertion cycles wires

50-micron gold-plated contacts improve signal integrity

Available in lengths up to 100ft

Lifetime warranty

Specifications

General	Info
---------	------

Гуре	Cable		
Standard	ANSI/TIA-568.2-D;ISO/IEC 11801-1	Warranty Type	Lifetime
eatures	PoE (Power Over Ethernet)	Application Sector	Commercial, Industrial, Residential
JPC Number	757120434085	Country Of Origin	Mexico
Product Line	C2G	Color	Blue

Dimensions

Product Length US 1.0 FT Cable Length 1 ft

Listing Agencies / 3rd Party Agencies

CE Certified	Yes	REACH Compliant	Yes
Buy American Act C	ompliance		
TAA Compliant	Yes		
Technical Information	on		
Jacket Material	PVC (Polyvinyl Chloride)	Wire Gauge	24 AWG
Jacket Application	Riser Rated	Shielded/Unshielded	Unshielded
Shield Type	UTP	Cable Type	Booted, Ethernet Patch Cable, Snagless, Unshielded (UTP)
Jacket Rating	CMR Rated	Cable Diameter	5.5 mm
Connector 2	RJ-45 Male	Connector 1	RJ-45 Male
Operating Temperatur	e -20°-75°C, -4°-167°F		