

This Cat6 cable meets stringent TAA compliant requirements and is approved for use in United States government projects and facilities. This Snagless Unshielded Cat6 network cable is designed for network adapters, hubs, switches, routers, servers and more. Meets or exceeds all ANSI/TIA-568.2-D Category 6 industry standards for supporting a wide variety of applications, including 1000BASE-T (1 Gigabit Ethernet). Constructed with premium, made in the USA copper cabling with enhanced 600 MhZ maximum frequency for increased performance over standard Cat6 cables. The molded, snagless boot prevents unwanted cable snags during installation and provides extra strain relief. Available in a wide variety of colors to easily color-code your network installation.

Features & Benefits

TAA-compliant

Constructed with high quality, made in the USA raw cable for consistent, reliable performance

Snagless RJ45 connector design protects clips from being easily snapped Standard RJ45 connectors and unshielded twisted pair off – great for applications with high insertion cycles wires

50-micron gold-plated contacts improve signal integrity

Available in a variety of colors and lengths up to 100ft

Lifetime warranty

Specifications

General Info

Product Line	C2G	Color	Blue	
UPC Number	757120434627	Country Of Origin	Mexico	
Features	PoE (Power Over Ethernet)	Application Sector	Commercial, Industrial, Residential	
Standard	ANSI/TIA-568.2-D;ISO/IEC 11801-1	Warranty Type	Lifetime	
Туре	Cable			
Dimensions				
Product Length US	75.0 FT	Cable Length	75 ft	
Listing Agencies / 3rd Party Agencies				
CE Certified	Yes	REACH Compliant	Yes	

Buy American Act Compliance

TAA Compliant

Yes

Technical Information

Jacket Material	PVC (Polyvinyl Chloride)	Wire Gauge	24 AWG
Jacket Application	Riser Rated	Shielded/Unshielded	Unshielded
Shield Type	UTP	Cable Type	Booted, Ethernet Patch Cable, Snagless, Unshielded (UTP)
Jacket Rating	CMR Rated	Cable Diameter	5.6 mm
Connector 2	RJ-45 Male	Connector 1	RJ-45 Male
Operating Temperature	-20°-75°C, -4°-167°F		