



This Cat6 cable meets stringent TAA compliant requirements and is approved for use in United States government projects and facilities. This Snagless Unshielded Cat6 network cable is designed for network adapters, hubs, switches, routers, servers and more. Meets or exceeds all ANSI/TIA-568.2-D Category 6 industry standards for supporting a wide variety of applications, including 1000BASE-T (1 Gigabit Ethernet). Constructed with premium, made in the USA copper cabling with enhanced 600 MhZ maximum frequency for increased performance over standard Cat6 cables. The molded, snagless boot prevents unwanted cable snags during installation and provides extra strain relief. Available in a wide variety of colors to easily color-code your network installation.

Features & Benefits

TAA-compliant	Constructed with high quality, made in the USA raw cable for consistent, reliable performance
Snagless RJ45 connector design protects clips from being easily snapped off – great for applications with high insertion cycles	Standard RJ45 connectors and unshielded twisted pair wires
50-micron gold-plated contacts improve signal integrity	Available in a variety of colors and lengths up to 100ft

Lifetime warranty

Specifications

General Info

57120434825 oE (Power Over Ethernet) NSI/TIA-568.2-D;ISO/IEC 11801-1	Color Country Of Origin Application Sector Warranty Type	Black Mexico Commercial, Industrial, Residential Lifetime				
oE (Power Over Ethernet) NSI/TIA-568.2-D;ISO/IEC 11801-1	Application Sector	Commercial, Industrial, Residential				
NSI/TIA-568.2-D;ISO/IEC 11801-1						
	Warranty Type	Lifetime				
able						
Type Cable						
Dimensions						
).0 FT	Cable Length	50 ft				
Listing Agencies / 3rd Party Agencies						
	REACH Compliant	Yes				
		rty Agencies				

Buy American Act Compliance

Yes

TAA Compliant

Technical Information

Jacket Material	PVC (Polyvinyl Chloride)	Wire Gauge	24 AWG
Jacket Application	Riser Rated	Shielded/Unshielded	Unshielded
Shield Type	UTP	Cable Type	Booted, Ethernet Patch Cable, Snagless, Unshielded (UTP)
Jacket Rating	CMR Rated	Cable Diameter	5.6 mm
Connector 2	RJ-45 Male	Connector 1	RJ-45 Male
Operating Temperature	-20°-75°C, -4°-167°F		