



C2G  
**25ft (7.6m) TAA-Compliant F-Series Cat6 Snagless Unshielded (UTP) Network Cable - White**  
Part No. AVD\_CG\_C2G43584



This Cat6 cable meets stringent TAA compliant requirements and is approved for use in United States government projects and facilities. This Snagless Unshielded Cat6 network cable is designed for network adapters, hubs, switches, routers, servers and more. Meets or exceeds all ANSI/TIA-568.2-D Category 6 industry standards for supporting a wide variety of applications, including 1000BASE-T (1 Gigabit Ethernet). Constructed with premium, made in the USA copper cabling with enhanced 600 MhZ maximum frequency for increased performance over standard Cat6 cables. The molded, snagless boot prevents unwanted cable snags during installation and provides extra strain relief. Available in a wide variety of colors to easily color-code your network installation.

## Features & Benefits

TAA-compliant

Constructed with high quality, made in the USA raw cable for consistent, reliable performance

Snagless RJ45 connector design protects clips from being easily snapped off – great for applications with high insertion cycles

Standard RJ45 connectors and unshielded twisted pair wires

50-micron gold-plated contacts improve signal integrity

Available in a variety of colors and lengths up to 100ft

Lifetime warranty

## Specifications

### General Info

Product Line	C2G	Color	White
UPC Number	757120435846	Country Of Origin	Mexico
Features	PoE (Power Over Ethernet)	Application Sector	Commercial, Industrial, Residential
Standard	ANSI/TIA-568.2-D;ISO/IEC 11801-1	Warranty Type	Lifetime
Type	Cable		

### Dimensions

Product Length US	25.0 FT	Cable Length	25 ft
-------------------	---------	--------------	-------

### Listing Agencies / 3rd Party Agencies

CE Certified	Yes	REACH Compliant	Yes
--------------	-----	-----------------	-----

---

## Buy American Act Compliance

---

TAA Compliant      Yes

---

## Technical Information

---

Jacket Material      PVC (Polyvinyl Chloride)      Wire Gauge      24 AWG

---

Jacket Application      Riser Rated      Shielded/Unshielded      Unshielded

---

Shield Type      UTP      Cable Type      Booted, Ethernet Patch Cable,  
Snagless, Unshielded (UTP)

---

Jacket Rating      CMR Rated      Cable Diameter      5.6 mm

---

Connector 2      RJ-45 Male      Connector 1      RJ-45 Male

---

Operating Temperature      -20°-75°C, -4°-167°F

---