

3ft (0.9m) TAA-Compliant F-Series Cat6 Non-Booted Unshielded (UTP) Network Cable - Yellow Part No. AVD CG C2G43650



This Cat6 cable meets stringent TAA compliant requirements and is approved for use in United States government projects and facilities. This non-booted unshielded Cat6 network cable is designed for network adapters, hubs, switches, routers, servers and more. Meets or exceeds all ANSI/TIA-568.2-D Category 6 industry standards for supporting a wide variety of applications, including 1000BASE-T (1 Gigabit Ethernet). Constructed with premium, made in the USA copper cabling with enhanced 600 MhZ maximum frequency for increased performance over standard Cat6 cables. Available in a wide variety of colors to easily color-code your network installation.

Features & Benefits

Constructed with high quality, made in the USA raw cable for consistent, reliable TAA-compliant performance

Standard RJ45 connectors and unshielded twisted pair

50-micron gold-plated contacts improve signal integrity

Available in lengths up to 25ft

| Available in lengths up t | to 25ft Lifetime wa | Lifetime warranty | | |
|---------------------------|----------------------------------|--------------------|-------------------------------------|--|
| Specifications | | | | |
| General Info | | | | |
| Product Line | C2G | Color | Yellow | |
| UPC Number | 757120436508 | Country Of Origin | Mexico | |
| Features | PoE (Power Over Ethernet) | Application Sector | Commercial, Industrial, Residential | |
| Standard | ANSI/TIA-568.2-D;ISO/IEC 11801-1 | Warranty Type | Lifetime | |
| Туре | Cable | | | |
| Dimensions | | | | |
| Product Length US | 3.0 FT | Cable Length | 3 ft | |
| Listing Agencies / 3rd | d Party Agencies | | | |
| CE Certified | Yes | REACH Compliant | Yes | |
| Buy American Act Co | mpliance | | | |
| | | | | |

| Jacket Material | PVC (Polyvinyl Chloride) | Wire Gauge | 24 AWG |
|-----------------------|--------------------------|---------------------|--|
| Jacket Application | Riser Rated | Shielded/Unshielded | Unshielded |
| Shield Type | UTP | Cable Type | Ethernet Patch Cable, Unbooted, Unshielded (UTP) |
| Jacket Rating | CMR Rated | Cable Diameter | 5.6 mm |
| Connector 2 | RJ-45 Male | Connector 1 | RJ-45 Male |
| Operating Temperature | -20°-75°C, -4°-167°F | | |