

This Cat6 cable meets stringent TAA compliant requirements and is approved for use in United States government projects and facilities. Protect a high speed network from noise and electromagnetic interference when connecting with our Snagless Shielded Cat6 patch cable. This Snagless Shielded Cat6 network cable is designed for network adapters, hubs, switches, routers, servers and more. Meets or exceeds all ANSI/TIA-568.2-D Category 6 industry standards for supporting a wide variety of applications, including 1000BASE-T (1 Gigabit Ethernet). Constructed with premium, made in the USA copper cabling with aluminum foil shield designed to counter EMI, RFI, and alien crosstalk. Available in a wide variety of colors to easily color-code a network installation.

pair wires

Constructed with high quality, made in the USA raw

Standard RJ45 connectors and unshielded twisted

Available in a variety of colors and lengths up to 25ft

cable for consistent, reliable performance

Features & Benefits

TAA-compliant

Snagless RJ45 connector design protects clips from being easily snapped off – great for applications with high insertion cycles

50-micron gold-plated contacts improve signal integrity

Lifetime warranty

Specifications

General Info

Product Line	C2G	Color	Blue	
UPC Number	757120437215	Country Of Origin	Mexico	
Features	PoE (Power Over Ethernet)	Application Sector	Commercial, Industrial, Residential	
Standard	ANSI/TIA-568.2-D;ISO/IEC 11801- 1	Warranty Type	Lifetime	
Туре	Cable			
Dimensions				
Product Length US	0.5 FT	Cable Length	0.5 ft	
Listing Agencies / 3rd Party Agencies				

CE Certified	Yes	REACH Compliant	Yes		
Buy American Act Compliance					
TAA Compliant	Yes				
Technical Information					
Jacket Material	PVC (Polyvinyl Chloride)	Wire Gauge	26 AWG		
Jacket Application	Riser Rated	Shielded/Unshielded	Shielded		
Shield Type	STP	Cable Type	Booted, Ethernet Patch Cable, Snagless		
Jacket Rating	CMR Rated	Cable Diameter	6 mm		
Connector 2	RJ-45 Male	Connector 1	RJ-45 Male		
Operating Temperature	-20°-75°C,-4°-167°F				