



C2G
3ft (0.9m) TAA-Compliant F-Series Cat6 Snagless Shielded (STP) Network Cable - Yellow
Part No. AVD_CG_C2G43766



This Cat6 cable meets stringent TAA compliant requirements and is approved for use in United States government projects and facilities. Protect a high speed network from noise and electromagnetic interference when connecting with our Snagless Shielded Cat6 patch cable. This Snagless Shielded Cat6 network cable is designed for network adapters, hubs, switches, routers, servers and more. Meets or exceeds all ANSI/TIA-568.2-D Category 6 industry standards for supporting a wide variety of applications, including 1000BASE-T (1 Gigabit Ethernet). Constructed with premium, made in the USA copper cabling with aluminum foil shield designed to counter EMI, RFI, and alien crosstalk. Available in a wide variety of colors to easily color-code a network installation.

Features & Benefits

TAA-compliant

Constructed with high quality, made in the USA raw cable for consistent, reliable performance

Snagless RJ45 connector design protects clips from being easily snapped off – great for applications with high insertion cycles

Standard RJ45 connectors and unshielded twisted pair wires

50-micron gold-plated contacts improve signal integrity

Available in a variety of colors and lengths up to 25ft

Lifetime warranty

Specifications

General Info

Product Line	C2G	Color	Yellow
UPC Number	757120437666	Country Of Origin	Mexico
Features	PoE (Power Over Ethernet)	Application Sector	Commercial, Industrial, Residential
Standard	ANSI/TIA-568.2-D;ISO/IEC 11801-1	Warranty Type	Lifetime
Type	Cable		

Dimensions

Product Length US	3.0 FT	Cable Length	3 ft
-------------------	--------	--------------	------

Listing Agencies / 3rd Party Agencies

CE Certified	Yes	REACH Compliant	Yes
--------------	-----	-----------------	-----

Buy American Act Compliance

TAA Compliant	Yes
---------------	-----

Technical Information

Jacket Material	PVC (Polyvinyl Chloride)	Wire Gauge	26 AWG
-----------------	--------------------------	------------	--------

Jacket Application	Riser Rated	Shielded/Unshielded	Shielded
--------------------	-------------	---------------------	----------

Shield Type	STP	Cable Type	Booted, Ethernet Patch Cable, Snagless
-------------	-----	------------	---

Jacket Rating	CMR Rated	Cable Diameter	6 mm
---------------	-----------	----------------	------

Connector 2	RJ-45 Male	Connector 1	RJ-45 Male
-------------	------------	-------------	------------

Operating Temperature	-20°-75°C, -4°-167°F
-----------------------	----------------------
