

C2G 15ft (4.6m) TAA-Compliant F-Series Cat6a Snagless Shielded (STP) Network Cable - Red Part No. AVD CG C2G43888



This Cat6a cable meets stringent TAA compliant requirements and is approved for use in United States government projects and facilities. This Snagless Shielded Cat6a patch cable is ideal for use with 10GBase-T ports and equipment, such as network adapters, hubs, switches, routers, DSL/cable modems and patch panels, and will protect a high speed 10 Gigabit network connection from noise and electromagnetic interference. For voice/data/video distribution, this cable will handle bandwidthintensive applications and drastically reduces both impedance and structural return loss (SRL). Meets or exceeds all ANSI/TIA-568.2-D Category 6A industry standards for supporting a wide variety of applications, including 10GBASE-T (10 Gigabit Ethernet). Constructed with premium, made in the USA copper cabling with aluminum foil shield designed to counter EMI, RFI, and alien crosstalk. Available in a wide variety of colors to easily color-code a network installation.

Features & Benefits

TAA-compliant

Snagless RJ45 connector design protects clips from being easily snapped off – great for applications with high insertion cycles

50-micron gold-plated contacts improve signal integrity

Lifetime warranty

Specifications

General Info

Product Line C2G Color Red UPC Number 757120438885 Country Of Origin Mexico Application Sector Features PoE (Power Over Ethernet) Commercial, Industrial, Residential ANSI/TIA-568.2-D; ISO/IEC 11801-Standard Warranty Type Lifetime 1 Cable Type Dimensions Product Length US 15.0 FT 15 ft Cable Length Listing Agencies / 3rd Party Agencies

Constructed with high quality, made in the USA raw cable for consistent, reliable performance

Standard RJ45 connectors and unshielded twisted pair wires

Available in a variety of colors and lengths up to 100ft

CE Certified	Yes	REACH Compliant	Yes
Buy American Act Compliance			
TAA Compliant	Yes		
Technical Information			
Jacket Material	PVC (Polyvinyl Chloride)	Wire Gauge	26 AWG
Jacket Application	Riser Rated	Shielded/Unshielded	Shielded
Shield Type	STP	Cable Type	Booted, Ethernet Patch Cable, Snagless
Jacket Rating	CMR Rated	Cable Diameter	6 mm
Connector 2	RJ-45 Male	Connector 1	RJ-45 Male
Operating Temperature	-20°-75°C,-4°-167°F		