



This Cat6a cable meets stringent TAA compliant requirements and is approved for use in United States government projects and facilities. This Snagless Shielded Cat6a patch cable is ideal for use with 10GBase-T ports and equipment, such as network adapters, hubs, switches, routers, DSL/cable modems and patch panels, and will protect a high speed 10 Gigabit network connection from noise and electromagnetic interference. For voice/data/video distribution, this cable will handle bandwidthintensive applications and drastically reduces both impedance and structural return loss (SRL). Meets or exceeds all ANSI/TIA-568.2-D Category 6A industry standards for supporting a wide variety of applications, including 10GBASE-T (10 Gigabit Ethernet). Constructed with premium, made in the USA copper cabling with aluminum foil shield designed to counter EMI, RFI, and alien crosstalk. Available in a wide variety of colors to easily color-code a network installation.

pair wires

Constructed with high quality, made in the USA raw

Standard RJ45 connectors and unshielded twisted

Available in a variety of colors and lengths up to 100ft

cable for consistent, reliable performance

## Features & Benefits

TAA-compliant

Snagless RJ45 connector design protects clips from being easily snapped off – great for applications with high insertion cycles

50-micron gold-plated contacts improve signal integrity

Lifetime warranty

## Specifications

## General Info

Product Line	C2G	Color	White	
UPC Number	757120439622	Country Of Origin	Mexico	
Features	PoE (Power Over Ethernet)	Application Sector	Commercial, Industrial, Residential	
Standard	ANSI/TIA-568.2-D;ISO/IEC 11801- 1	Warranty Type	Lifetime	
Туре	Cable			
Dimensions				
Product Length US	3.0 FT	Cable Length	3 ft	
Listing Agencies / 3rd Party Agencies				

CE Certified	Yes	REACH Compliant	Yes	
Buy American Act Compliance				
TAA Compliant	Yes			
Technical Information				
Jacket Material	PVC (Polyvinyl Chloride)	Wire Gauge	26 AWG	
Jacket Application	Riser Rated	Shielded/Unshielded	Shielded	
Shield Type	STP	Cable Type	Booted, Ethernet Patch Cable, Snagless	
Jacket Rating	CMR Rated	Cable Diameter	6 mm	
Connector 2	RJ-45 Male	Connector 1	RJ-45 Male	
Operating Temperature	-20°-75°C,-4°-167°F			